

showcase lighting

- Micro-sized design showcase lighting
- Unique optical design, fine surface treatment
- Perfect for your boutiques & retail experience
- Emphasize the value of product




SHOWCASE BY RUTEC

This is a breakthrough in small-scale innovation aimed at revolutionizing the lighting methods of store windows, ensuring that displayed items are visible without any obstacles. This sleek yet powerful product boasts excellent lighting performance and effectively enhances the presentation of showcased items.

Equipped with the latest generation of LED light sources, available in 3000 K and 4000 K light colors, this ensures high quality, efficiency, and exceptional color rendition. Its introduction completely transforms the lighting paradigm of display cabinets, allowing for the comprehensive showcasing of all merchandise.

With special optical lenses to enhance light distribution and minimize glare to ensure your perfect illumination experience.





Variety of styles

This is the perfect choice for displaying your products. Not only does it boast an exquisite appearance, but it also offers powerful functionality to make your product displays more enticing. This lighting fixture comes equipped with two types of bases, thin and thick, catering to different display needs and style preferences. The thin base provides a sleek, minimalist look, perfectly blending with the tabletop.


Furthermore, the thick base offers enhanced stability and elegance, featuring a diamond-patterned design that adds a touch of luxury and sophistication. This series delivers outstanding lighting effects, highlighting the beauty and brilliance of your products.


Whether used for commercial displays or home setups, it allows your products to exude a unique charm, ensuring exceptional display performance and a satisfying user experience.

Height adjustable

Liberal and flexible 360 degree rotation and adjustment in height and base for different applications whenever you require.

Its unique adjustable height feature ensures that you can adjust according to different display needs, allowing each piece of jewelry to receive proper illumination, thus showcasing its beauty and uniqueness.










Showcase lights-bend




Colours

9 Haze  4 Chrome  2 Black 

	Article number	LED Consumption	Constant Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
	7192X	3W	350 mA	270 lm	228 lm	30° (Lens)	3000K	90+
	7193X	3W	350 mA	270 lm	228 lm	30° (Lens)	3000K	90+






 Cut out : 14mm



Showcase lights-upright




Colours

9 Haze  4 Chrome  2 Black 

	Article number	LED Consumption	Constant Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
	7194x	3W	350 mA	270 lm	228 lm	30° (Lens)	3000K	90+
	7195x	3W	350 mA	270 lm	228 lm	30° (Lens)	3000K	90+



 Cut out : 14mm


Showcase lights-Adjustable



Colours

9 Haze 4 Chrome 2 Black


Article number	LED Consumption	Constant Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
7189x	3W	350 mA	270 lm	-	30° (Lens)	3000K	90+




⦿ Cut out : 25mm




WIRING DIAGRAM



C.C.



C.V.




C.C Accessory (Constant Current)




59220
59221
Type: TOP junction box

6 way series connection cord
3 way series connection cord
Length : 6"(15.24cm)



59222
Type: Driver connection

Driver connection cord
Length : 3.94"(10cm)



59223
Type: Connection

Connection cord
Length : 36"(91.44cm)



59228
59229
Type: Driver Plug

I/P: 100-240V,
O/P: 350mA/3-36VDC/max.8w
CE/UL/CUL
3W x 1-2 pcs



59230
Type: Driver

I/P: 100-277V,
O/P: 350mA/5-40VDC/max.20w
CE/ENEC/CCC/CUL
3W x 1-4 pcs



Goal line

This gate light, supremely lightweight, sleek, and flexible, injects innovation into the world of illumination. With no need for cumbersome installation procedures, it's easy to assemble and convenient to use. Comprising two vertical poles and one horizontal bar, the horizontal bar can rotate 360 degrees, offering a variety of color temperatures to swiftly refresh your space design. No worries, just pure inspiration and overflowing creativity.





► Customize your modular setup

Adapting adapt to various spaces, shapes, and sizes.

Goal Line

Diffuse Light Module

This is the ideal lighting choice for creating a harmonious atmosphere and ensuring even light distribution.




Goal Dot


Lens Module

Provides a balanced light effect where no area is left in the shadow, while simultaneously highlighting the most important subjects. This is the ideal solution for achieving accent lighting, with light cuts emphasizing the details you want to bring out.





71990
Linear pole




 Cut out : 14mm

71991
T pole





 Cut out : 14mm


Showcase lights-Goal Line



Colours

9 Haze  2 Black 

Article number	LED Consumption	Constant Voltage	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
7196x	3W	DC24V	351 lm	276 lm	120° (Lens)	3000K	90+
7197x	6W	DC24V	702 lm	547 lm	120° (Lens)	3000K	90+
7198x	9W	DC24V	1053 lm	828 lm	120° (Lens)	3000K	90+



Driver Accessory



59231
Type: Driver

I/P: 220-240V,
O/P: 24VDC/max.15w
CE/TUV/UKCA



59232
Type: Driver


I/P: 120V,
O/P: 24V/max.12w
CE/CUL/FCC

Showcase lights-Goal Dot




Colours
9 Haze 2 Black

Article number	LED Consumption	Constant Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
7186x	4.8W	250 mA	486 lm	-- lm	30° (Lens)	3000K	90+
7187x	9.6W	500 mA	972 lm	-- lm	30° (Lens)	3000K	90+
7188x	14.4W	750 mA	1458 lm	-- lm	30° (Lens)	3000K	90+



Line

The best lighting solution for display shelves, designed to create a harmonious atmosphere and provide even light distribution, making it an ideal lighting choice.



Chips



61999
Clip (Included in fixture)


Showcase lights-Line



Colours

9 Haze ☐ 2 Black ☒

Article number	LED Consumption	Constant Voltage	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
7176x	3W	DC24V	351 lm	276 lm	120° (Lens)	3000K	90+
7177x	6W	DC24V	702 lm	547 lm	120° (Lens)	3000K	90+
7178x	9W	DC24V	1053 lm	828 lm	120° (Lens)	3000K	90+




Showcase lights-Dot



Colours

9 Haze ☐ 2 Black ☒

Article number	LED Consumption	Constant Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
7166x	4.8W	250 mA	486 lm	-- lm	30° (Lens)	3000K	90+
7167x	9.6W	500 mA	972 lm	-- lm	30° (Lens)	3000K	90+
7168x	14.4W	750 mA	1458 lm	-- lm	30° (Lens)	3000K	90+






The petite recessed light, boasting a 41mm outer diameter and standing at a height of less than 3 centimeters, is a slim and versatile lighting solution. With its unique swaying and zooming capabilities, this light fixture is perfect for enhancing furniture cabinets. Its compact size and innovative features make it an ideal choice for adding both style and functionality to your living spaces.



ALU53002




ALU53012



Article number	ALU53002
LED Consumption	2W
Current	700 (mA)
Lumen	161 (lm)
Beam Angle	25°(Lens)
CCT	3000K
CRI	90+
Article number	ALU53202
LED Consumption	2W
Current	700 (mA)
Lumen	161 (lm)
Beam Angle	15°~30°(Lens)
CCT	3000K
CRI	90+
Colours :	<div> <div>1 White</div> <div>2 Black</div> <div>5 Anodized Alum.</div> </div>



ALU53103



ALU53113

Article number ALU53103





LED Consumption	1W
Current	350 (mA)
Lumen	95 (lm)
Beam Angle	30° (Lens)
CCT	3000K
CRI	90+


Article number ALU53113


LED Consumption	1W
Current	350 (mA)
Lumen	95 (lm)
Beam Angle	30° (Lens)
CCT	3000K
CRI	90+

Colours :  3 Gold

Designed for shelves and niches with a minimum thickness of 15 mm.
The very small size, make it ideal for the setting up of display and showcases for jewellers or museums.



 Cut out : 10.5mm

 Cut out : 18mm





Showcase lights-Chameleon eyes




Colours

Body: 1 Black ☒ 2 White ☐

Article number	LED Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
ALU5313X	4W	350 mA	408lm	-- lm	15°/24°/36° (Lens)	3000K	90+



 Cut out : 55mm





Showcase lights-Standard




Colours

Body: 1 Black ☒ 2 White ☐

Article number	LED Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
ALU5312X	2W	700 mA	161 lm	138 lm	18°/23°/33° (Lens)	3000K	90+



 Cut out : 35mm





The most powerful spotlight

This recessed premium display spotlight is designed to showcase the beauty of fine items. Despite its small size, it carries powerful lighting capabilities, adding a touch of brilliance to your display environment. With its 360° rotation and 90° tilt features, it grants you flexible control over lighting, ensuring every detail of your premium items is highlighted.

Moreover, this light fixture is available in two sizes to accommodate different display spaces. It is an ideal choice for both commercial showcases and personal collections. Its exquisite design complements its outstanding lighting performance, bringing elegance and sophistication to your displays. Wherever it is used, this spotlight will provide an extraordinary display experience with its versatility and stylish design.




Showcase lights-spot



Colours

Body : Black

Article number	LED Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
73320	3W	700 mA	193 lm	38 lm	18°~35° (Lens)	3000K	90+



Cut out : 8mm

Optional Accessory



7331X
Color filter



7331X
please contact with our sales rep for more info




Showcase lights-spot



Colours

Body: 3 Brass 2 Black

Article number	LED Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
7333X	1W	300 mA	96 lm	82 lm	25°/35°/50° (Lens)	3000K	90+



Cut out : 8mm

Optional Accessory



S-014
Snoot


Showcase lights-spot



Colours

Body: 3 Brass 2 Black

Article number	LED Consumption	Current	LED Lumen	Delivered Lumen	Beam Angle	CCT	CRI
7334X	3W	700mA	210 lm	173 lm	15°/27°/32° (Lens)	3000K	90+



Cut out : 8mm

Optional Accessory



H-003
Honeycomb louver








DS-004
Asymmetric Diffusers



DS-005
Diffusers



WIRING DIAGRAM





Professional-grade optical lens


Crafted with a combination of high-quality multi-layer lenses to enhance light transmission, providing high adjustability, uniform light output, and a wide zoom range.

We recommend this professional mini spotlight, specifically designed for high-end display needs. It is particularly well-suited for focusing on delicate small items, ensuring excellent illumination even for the smallest artifacts.


This light fixture features a mini track design, occupying minimal space, and can be easily adjusted without tools, adapting seamlessly to changes in the display space. It offers a vertical tilt range of 0° to 90° and a horizontal rotation capability of 355°, allowing for flexible positioning and configuration based on the display items' location and angle. Available with color filter and Customization gobo

High-precision optical components ensure clear beam outlines and high illumination uniformity, guaranteeing that every item is presented in the best possible light, drawing all attention to the exhibits themselves.

This professional mini spotlight is the ideal choice for museums, galleries, high-end retail stores, and other display spaces that require precise lighting. We believe it will provide your exhibits with outstanding illumination, allowing every piece to be showcased in its most perfect form.



Showcase Spot-Framing



Article number **73302**

Fixture Consumption 2.3W

Voltage 24 VDC

Lumen 164 (lm)

Beam Angle 18°~35° (Lens)

CCT 3000K

CRI 90+

Colour Black ■



7331X
Color filter



7331X
please contact with our sales rep for more info



Circle



Trapezoid



Irregular shape




Square



Triangle

Showcase Spot



Fixture Consumption	1.2W
Voltage	24 VDC
Delivered Lumen	96 (lm)
Beam Angle	25°/35°/50° (Lens)
CCT	3000K
CRI	90+
Colour	Black ■





Snoot

73232



Spot
73232





H(m)	D(m)	E(lx)
25°		
1.0	0.46	163
2.0	0.92	40
3.0	1.38	18
4.0	1.84	10
5.0	2.31	6

73242



Spot
73242





H(m)	D(m)	E(lx)
35°		
1.0	0.60	153
2.0	1.20	38
3.0	1.80	17
4.0	2.41	9
5.0	3.01	6


73252



Spot
73252



H(m)	D(m)	E(lx)
50°		
1.0	0.92	82
2.0	1.84	20
3.0	2.76	9
4.0	3.68	5
5.0	4.60	3



Fixture Consumption	2.6W
Voltage	24 VDC
Delivered Lumen	185 (lm)
Beam Angle	16°/25°/45°/60° (Lens)
CCT	3000K
CRI	90+
Colour	Black ■



Honeycomb louver



Asymmetric Diffusers





Diffusers

73262



16°

Spotlight
73262





H(m)	D(m)	E(lx)
16°		
1.0	0.29	1024
2.0	0.59	256
3.0	0.88	113
4.0	1.17	63
5.0	1.46	40

73272



25°

Spotlight
73272





H(m)	D(m)	E(lx)
25°		
1.0	0.43	569
2.0	0.87	142
3.0	1.30	63
4.0	1.74	35
5.0	2.17	22

73282



45°

Spotlight
73282





H(m)	D(m)	E(lx)
45°		
1.0	0.82	195
2.0	1.64	48
3.0	2.46	21
4.0	3.27	12
5.0	4.09	7

73292






60°

Spotlight
73292



H(m)	D(m)	E(lx)
60°		
1.0	1.05	123
2.0	2.10	30
3.0	3.15	13
4.0	4.20	7
5.0	5.24	4

Showcase Spot



Article number	73402, 73412, 73422, 73432
Fixture Consumption	6.5W
Voltage	24 VDC
Lumen	799 (lm)
Delivered Lumen	668 (lm)
Beam Angle	24°/30°/40°/60° (Lens)
CCT	3000K
CRI	90+
Colour	Black ■



7344X
Honeycomb louver



7344X
Asymmetric Diffusers



7344X
Diffusers



7344X
Barndoor

* Barndoor is not suitable for vertical installation

Article number	73502, 73512, 73522, 73532
Fixture Consumption	6.5W
Voltage	24 VDC
Lumen	799 (lm)
Delivered Lumen	543 (lm)
Beam Angle	24°/30°/40°/60° (Lens)
CCT	3000K
CRI	90+
Colour	Black ■



7354X
Honeycomb louver



7354X
Asymmetric Diffusers



7354X
Diffusers



7354X
Barndoor

* Barndoor is not suitable for vertical installation



Article number	73602
Fixture Consumption	6.5W
Voltage	24 VDC
Lumen	799 (lm)
Delivered Lumen	317 (lm)
Beam Angle	15°~40° (Lens)
CCT	3000K
CRI	90+
Colour	Black ■





24°

Spotlight





H(m)	D(m)	E(lx)
24°		
1.0	0.43	2123
2.0	0.87	530
3.0	1.30	235
4.0	1.73	130
5.0	2.17	84



30°

Spotlight





H(m)	D(m)	E(lx)
30°		
1.0	0.53	1619
2.0	1.06	404
3.0	1.58	179
4.0	2.11	101
5.0	2.64	64



40°

Spotlight





H(m)	D(m)	E(lx)
40°		
1.0	0.75	928
2.0	1.50	232
3.0	2.25	103
4.0	2.99	58
5.0	3.74	37



60°

Spotlight





H(m)	D(m)	E(lx)
60°		
1.0	1.09	458
2.0	2.19	114
3.0	3.28	50
4.0	4.38	28
5.0	5.47	18



15°

Spotlight





H(m)	D(m)	E(lx)
15°		
1.0	0.28	1079
2.0	0.56	269
3.0	0.84	119
4.0	1.13	67
5.0	1.41	43



40°

Spotlight



H(m)	D(m)	E(lx)
40°		
1.0	0.69	538
2.0	1.39	134
3.0	2.08	59
4.0	2.78	33
5.0	3.47	21

Showcase Panel



Article number	73202	
Fixture Consumption	4.3W	(72pcs)
Voltage	24 VDC	
Delivered Lumen	146 (lm)	
Beam Angle	120°	
CCT	3000K	
CRI	90+	
Colour	Black ■	



Article number	73212	
Fixture Consumption	8.7W	(144pcs)
Voltage	24 VDC	
Delivered Lumen	287 (lm)	
Beam Angle	120°	
CCT	3000K	
CRI	90+	
Colour	Black ■	






Article number	73222	
Fixture Consumption	13W	(216pcs)
Voltage	24 VDC	
Delivered Lumen	448 (lm)	
Beam Angle	120°	
CCT	3000K	
CRI	90+	
Colour	Black ■	



TRIM MODELS DIMENSIONS

73232 / 73242 / 73252




H(m)	D(m)	E(lx)
120°		
1.0	2.81	13
2.0	5.62	3
3.0	8.42	1
4.0	11.23	0
5.0	14.04	0



SHOWCASE TRACK 24V

system





Showcase Track 24V

Innovative design of ultra-micro structure, there are designs for recessed, ceilings, and pendent.

They adopt micro-shaped and exquisite magnetic designs.

Because they are very easy to install.

They can be easily and quickly adjusted according to various professional lighting standards to meet the needs of lighting design.

Suitable for a variety of professional lighting solutions including widely used in luxury chain counter lighting, window lighting, exhibition lighting, hospitality, home lighting, etc.

The ultimate solution




Showcase Track 24V system

Thanks to the exquisite structure of the 11 mm track design, the series has strong capabilities to fit into stenosis space. Its magnetic adaptor provides a convenient and prompt replacement module. The best solution for the showcase, shelf, niche, etc.



Showcase Track 24V Display system



Quickinfo

GENERAL

Recessed

ELECTRICAL

NON DIM

PHYSICAL

Aluminium

Spray powder

Description

The ceiling, wall, and shelf aren't the limitations of the series.

The showcase for the shopping mall and museum also can be lit up.

Its ultimate performance lets any product be highlighted by the display system.


The featured product in the store will become an eye-catching point immediately.

Panel



Spot






stem track


Colour Black ■

INSTALLATION TRACK

Article number	L (mm)	TYPE
73092	19.69" (500mm)	Stem



Showacase Track 24V







Showcase Track 24V diversity installation

The track for the series has multi-type functions.
Such as surface mounted, recessed trimless, pendant, and top-down pendant type.
Furthermore, the track has three default lengths, 1 m, 1.5 m, and 2 m, for the choice.
What's even more pleasant is the track can be cut on-site.
In other words, users can customize the specific length of the track to meet various requirements.


Recessed



Surface mounted



Pendant



Showcase Track 24V

Surface Mounted system



Quickinfo

GENERAL

Surface Mounted

Recessed

ELECTRICAL

NON DIM

PHYSICAL

Aluminium

Spray powder

Description

The incredible 11 mm profile size that characterizes the program enhances the light's flexibility and its relationship with the architecture.

The surface-mounted profile track gives the architectural designer the ability to outline the most distinctive artistic expressions inside the space.

Max wattage linkable per loop for 24V, 96W, class 2 driver. (FOR U.S.)


Max wattage linkable per loop for 24V, 100W. (FOR EU)

Panel



Spot








surface mounter track

Colour Black ■

INSTALLATION TRACK

Article number	L (mm)	TYPE
73002	39.37" (1000mm)	Surface Mounted
73012	59.06" (1500mm)	Surface Mounted
73022	78.74" (2000mm)	Surface Mounted



△ Cut out : 15/32"X1/2" (12X13mm)







pendant track

Colour Black ■

INSTALLATION TRACK









Article number	L (mm)	TYPE
73062	39.37" (1000mm)	Pendant
73072	59.06" (1500mm)	Pendant
73082	78.74" (2000mm)	Pendant



Article number	TYPE
73910	Horizontal corner




CIRCUIT JOINT

1		Article number	TYPE
		73900	Horizontal corner L Circuit joint
2		Article number	TYPE
		73901	Power joint Length : 78.74" (2000mm)
3		Article number	TYPE
		73902	Circuit joint Length : 0.59" (15mm)
4		Article number	TYPE
		73903	Circuit joint Length : 11.81" (300mm)
5		Article number	TYPE
		73904	I Circuit joint
6		Article number	TYPE
		73905	Blank cover Length : 78.74" (2000mm)
7		Article number	TYPE
		73906	Vertical corner Right angle seat
8		Article number	TYPE
		73907	End cap


* Tail cap has break-off holes for self-trimming.





Showcase Track 24V

Pendant system



Quickinfo

GENERAL

Pendant

ELECTRICAL

NON DIM

PHYSICAL

Aluminium

Spray powder

Description

Imagine creating a 3 dimension artificial works of art floating above in the space. This pendant system provides the possibility of creativity for the users and designers.

It gets rid of the shackles of the surface, allows endless imagination and creativity to emanate from each idea endlessly.

Max wattage linkable per loop for 24V, 96W, class 2 driver. (FOR U.S.)

Max wattage linkable per loop for 24V, 100W. (FOR EU)

Panel



Spot



CIRCUIT JOINT



Article number	TYPE
73901	Power joint Length : 78.74" (2000mm)



Article number	TYPE
73902	Circuit joint Length : 0.59" (15mm)



Article number	TYPE
73904	I Circuit joint



Article number	TYPE
73905	Blank cover Length : 78.74" (2000mm)



Article number	TYPE
73908	End cap




Article number	TYPE
73909	Reinforced joint


CEILING FASTENER / CABLE SUSPENSION



Article number	TYPE
73920	Pendant Kit




Article number	TYPE
73921	Pendant Kit for power connection without power cord (FOR EU)



Article number	TYPE
73922	Pendant Kit for power connection without power cord (FOR U.S.)





9

8

6

7

2

1

5

4

3

Spot

Showcase Track 24V

Recessed Trimless system



Quickinfo

GENERAL

Recessed Trimless

ELECTRICAL

NON DIM

PHYSICAL

Aluminium

Spray powder

Description

Surprising to the 5.8mm width of the track's inner length.

The recessed trimless track creates an extremely neat surface wherever it is installed.

Combining with the horizontal and vertical corner profiles, this system significantly reduces the sensitivity of oppressive in the boutique area.

Exquisite, elegant, luxurious, and grandeur are its deputation.

Max wattage linkable per loop for 24V, 96W, class 2 driver. (FOR U.S.)


Max wattage linkable per loop for 24V, 100W. (FOR EU)

Panel



Spot







recessed trimless track


Colour Black ■

INSTALLATION TRACK



Article number	L (mm)	TYPE
73032	39.37" (1000mm)	Recessed Trimless
73042	59.06" (1500mm)	Recessed Trimless
73052	78.74" (2000mm)	Recessed Trimless



▲ Cut out : 13/16"X15/32"(20X12mm)



Article number	TYPE
73911	Trimless recessed horizontal corner



Article number	TYPE
73912	Trimless recessed vertical corner





CIRCUIT JOINT

Article number	TYPE
73901	Power joint (For EU)
73901US	Power joint (For AM) Length : 78.74" (2000mm)



Article number	TYPE
73902	Circuit joint Length : 0.59" (15mm)



Article number	TYPE
73904	I Circuit joint




Article number	TYPE
73905	Blank cover Length : 78.74" (2000mm)



Article number	TYPE
73906	End cap




Article number	TYPE
73930	Reinforced joint (2 Pieces)





Showcase Track 24V

Pendant system



Quickinfo

GENERAL

Pendant

ELECTRICAL

NON DIM

PHYSICAL

Aluminium

Spray powder

Description

Want to create an eye-catching work of art?

The Showcase Track up-down pendant system is your choice.

According to the two directions of the luminous surface, up-down pendant system gives a diverse performance in 3 dimensions. Lights aren't just for decoration and illuminated anymore.

It becomes an eye-catching work of art for intellectual, emotional, and rational.

Max wattage linkable per loop for 24V, 96W, class 2 driver. (FOR U.S.)

Max wattage linkable per loop for 24V, 100W. (FOR EU)

Panel



Spot







pendant track up and down

Colour Black ■

INSTALLATION TRACK








Article number	L (mm)	TYPE
73102	39.37" (1000mm)	Up-down Pendant
73112	59.06" (1500mm)	Up-down Pendant
73122	78.74" (2000mm)	Up-down Pendant






Article number	TYPE
73913	Horizontal corner





CIRCUIT JOINT

	Article number	TYPE
	73901	Power joint Length : 78.74" (2000mm)
	Article number	TYPE
	73902	Circuit joint Length : 0.59" (15mm)
	Article number	TYPE
	73926	Circuit joint Length : 2.76" (70mm)
	Article number	TYPE
	73904	I Circuit joint
	Article number	TYPE
	73905	Blank cover Length : 78.74" (2000mm)
	Article number	TYPE
	73927	End cap
	Article number	TYPE
	73930	Reinforced joint (2 Pieces)

CEILING FASTENER / CABLE SUSPENSION


	Article number	TYPE
	73923	Pendant Kit
	Article number	TYPE
	73924	Pendant Kit for power connection without power cord (FOR EU)
	Article number	TYPE
	73925	Pendant Kit for power connection without power cord (FOR U.S.)







Installation method 1





Installation method 2

